



# IF30

## Fixed Reader

- Dense reader mode enables superior adjacent dock door reading
- Conveyor reading up to 1600 fpm
- Directly monitors and controls presence detectors and signal lights
- Multi-protocol reading and writing of UHF RFID tags
- Factory configurable to operate in 865MHz, 869MHz or 915MHz RFID bands
- On-board device management
- Built in power supply

The IF30 is a cost-effective, high performance fixed reader that reliably reads and writes UHF RFID tags in “RF noisy” environments. The IF30’s receive sensitivity enables large populations of tags to be interrogated at high speeds, which is critical to many use cases involving dock doors, portals and conveyors. In addition to reading tags at distances over 15 feet (4.6 meters), the IF30 can filter tag data to prevent sending redundant information to the host system.

With best in class Dense Reader Mode performance, the IF30 fixed reader allows users to grow their RFID operations to include multiple dock doors in close proximity, thus enabling accurate, automated receiving and shipment verification. This drives more effective put away processes.

Increased receive sensitivity allows the IF30 to interrogate weaker/unreadable tags that often lead to expensive exception handling processes and slower supply chain throughput.

Unlike all competitors, the IF30 has a built-in power supply and 4 mono-static RF ports which reduce the costs and complexity at installation with fewer component pieces to complete the overall solution.

Continuing to focus on keeping the costs of ancillary equipment and installation low, the IF30 fixed reader includes powered general purpose input/output (GPIO) circuitry, which allows direct monitoring and/or controlling of peripherals such as presence detectors and signal lights without requiring extra devices and power supplies to facilitate the connection.

Intermec SmartSystem® Foundation, a device management system included on the IF30, lets you view and configure all of the settings contained in the device from one convenient location allowing for a quicker set-up.

SmartSystems-enabled devices appear on an administrator’s console, providing real-time visibility to device status and information, and centralized access to remote devices like the IF30 reader.

The intuitive console allows administrators to change device settings, send firmware upgrades, update software applications, and execute other changes directly from the console to save time and significantly cut costs.

The IF30 reader is also supported by Intermec’s RFIDeploy Services which

provide process analysis, site analysis and installation. By deploying the full suite of services, your system performance will be guaranteed for 18 months, or you may simply select the service that will facilitate the completion of your RFID roll out.

In support of a global supply chain, the IF30 is FCC and ETSI certified, and is factory configured to operate in RFID frequency bands 865MHz, 869MHz and 915MHz.

#### Physical Description

The IF30 is an UHF fixed reader that can be factory configured to operate in RFID frequency bands: 865MHz, 869MHz and 915MHz. In addition to performing both read and write functions, the IF30 has built in general purpose input output (GPIO), 4 mono-static RF ports and a built-in power supply.

#### Physical Characteristics

**Length:** 32.35 cm (12.74 in)

**Width:** 22.60 cm (8.90 in)

**Height:** 8.25 cm (3.25 in)

**Weight:** 6.75lbs (3.06 Kg)

#### Environment

**Operating Temperature:** -20°C to 55°C (-13° F to 131° F)

**Storage Temperature:** -30°C to 75°C (-22° F to 167° F)

**Humidity:** 10% to 90% (Non-condensing)

**Enclosure:** IP53

#### Standard Features

**Communications Interface options:** Ethernet 10/100BaseT and RS232 for configuration

**Configuration:** Internal web Graphical User Interface (GUI)

**General Purpose Input/Output (GPIO):** Four input (0-40VDC) and four output (0-48VDC .25 amp) circuits, 500ma 12VDC power

#### Antenna Connections

**Four – Connectors:** FCC-Reverse SMA, ETSI Standard SMA, 30 dBm to 10dBm RF power output software controlled

#### Power

110-240 VAC auto ranging

Power Supply is internal and included

Duty Cycle: 100%

#### RFID Frequency Ranges

865, 869 and 915 MHz

#### Tag Air Interfaces

Fairchild G1

ISO 18000-6b

ISO 18000-6c

Philips Version 1.19

EPCglobal UHF Gen 2

#### Application Protocols

ANSI INCITS 256:2001

Intermec Basic Reader Interface

#### Connectivity

Ethernet IPv4 & IPv6

RS232 for configuration

#### Software

Syslog Client

HTTP/HTTPS Web Server

TFTP Client

DHCP Client

DNS Client

SNTP Client

#### Security

OpenSSL

Radius configuration login

#### Device Management

SNMP

Intermec SmartSystems™ client

Wavelink Avalanche™ Client

#### Accessories

Antennas, antenna cables, mounting bracket

#### Standards

AIAG B-11

ANSI MH10.8.4

ISO/IEC WD18000 Part 6

IF30 uses the IM5 module, which is EPC Certified

Compliant and EPC Certified Interoperable.

#### Restrictions on Use

Some approvals and features may vary by country and may change without notice.

Please check with your local Intermec sales office for further information.

#### Disclaimer

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.

#### North America

##### Corporate Headquarters

6001 36th Avenue West  
Everett, Washington 98203  
Phone: (425) 348-2600  
Fax: (425) 355-9551

##### South America & Mexico

##### Headquarters Office

Newport Beach, California  
Phone: (949) 955-0785  
Fax: (949) 756-8782

#### Europe/Middle East &

##### Africa Headquarters Office

Reading, United Kingdom  
Phone: +44 118 923 0800  
Fax: +44 118 923 0801

##### Asia Pacific

Headquarters Office  
Singapore  
Phone: +65 6303 2100  
Fax: +65 6303 2199

#### Internet

www.intermec.com  
Worldwide Locations:  
www.intermec.com/locations

#### Sales

Toll Free NA: (800) 934-3163  
Toll in NA : (425) 348-2726  
Freephone ROW: 00 800 4488 8844  
Toll ROW : +44 134 435 0296

#### OEM Sales

Phone: (425) 348-2762

#### Media Sales

Phone: (513) 874-5882

#### Customer Service and Support

Toll Free NA: (800) 755-5505  
Toll in NA : (425) 356-1799



Copyright © 2007 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611799-01B 03/07

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.